



Specifications Multipack 4x Philips  
LED Downlight Coreline DN142B  
Aluminium White 19.2W 2300lm 60D -  
830 Warm White | Cutout 200mm -  
IP20 - White Reflector

[View Product](#)

## General Information

|                          |                                      |
|--------------------------|--------------------------------------|
| SKU                      | 253055                               |
| EAN                      | 8719157059510                        |
| manufacturer_code        | 8719157059510                        |
| Brand                    | Philips                              |
| Manufacturer Name        | Multipack 4x DN142B 20S/830 PSU-E WR |
| Any Lamp all-in warranty | 5 Years                              |
| Average Lifetime (h)     | 50000                                |

## Technical Information

|                             |                   |
|-----------------------------|-------------------|
| Emergency Lighting          | No Emergency Unit |
| Tiltable                    | No                |
| Technology                  | LED Integrated    |
| Replaces (Watt)             | 2x18              |
| Wattage                     | 19.2W             |
| Voltage (V)                 | 220-240           |
| Dimmable                    | Not Dimmable      |
| Colour Code                 | 830 Warm White    |
| Colour temperature (Kelvin) | 3000 Warm White   |
| Colour Rendering (Ra)       | 80-89             |
| Colour of Light             | White             |

|                       |                                    |
|-----------------------|------------------------------------|
| Light Colour Options  | Single Color                       |
| Beam Angle (degree)   | 60                                 |
| Luminous Flux (Lumen) | 2300lm                             |
| Lumen per watt        | 120                                |
| Power factor          | >0.95                              |
| Unified Glare Rating  | < 25 - for hallways and staircases |
| Optical Cover         | PC (Polycarbonate)                 |
| Product Type Category | LED Downlight                      |

## Fixture Information

|                        |                               |
|------------------------|-------------------------------|
| Mounting Method        | Recessed                      |
| Cut out (mm)           | 200                           |
| IP-Rating              | IP20                          |
| Impact Protection (IK) | IK02 - 0.20 joule             |
| Operating Temperature  | -20 to +40                    |
| Housing                | Aluminium                     |
| Colour of the Fixture  | White                         |
| Fixture Connection     | PI [Push-in connector 6-pole] |
| Series                 | DN142B                        |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 105 |
| Diameter (mm) | 216 |

 **Sensor Information** Order from the **largest lighting specialist** in Europe  **Customised** quotation

Type of sensor



**Up to 7 years warranty**

No Sensor



**Easy** return process